
WICANDERS

Everyday comfort.
Lifetime performance.



AMORIM CORK FLOORING



WICANDERS

Wicanders has a legacy that goes back to 1868. It is part of Amorim Cork Flooring, the global leading brand in cork-based flooring, present in more than 80 countries worldwide. Its promise is to provide Floors for Living, ready for real life, for our home and office, for our different rhythms, for our family and pets. For all those wonderful and simple, yet sometimes unexpected moments, thanks to Wicanders durability and **performance**.

Over the years, Wicanders has developed sustainable flooring with exclusive properties due to its cork benefits. By combining state of the art technology with the exclusive natural properties of cork, a higher standard of **comfort** in flooring is achieved. Available with cork, wood and stone looks, its products are able to provide a silent and thermally insulated environment that endures impacts and is very comfortable to walk and stand on.

Everyday comfort, lifetime performance.

AMORIM CORK FLOORING



Created by Humans, inspired by Nature



AMAZING COMFORT

Welcome to your amazing new home

Come in, put your shoes aside, and relax. This is about family and happiness. The exact place where you should dance free or run wild after your kids. And nothing must stop this.

That's why we offer the perfect ground to your family's everyday life. Safe and cozy, healthy and memorable. Our floors provide amazing comfort features and are designed to perform. And because family it's also future, we have been developing sustainable products, based on cork, a revolutionary raw material. It's 100% natural, reusable and recyclable

We are glad to welcome you in your amazing new home.



BEING
GREEN
BEING
UNIQUE

CORK: INSPIRED BY NATURE

Cork is the outer bark of the cork oak tree, a slowly growing tree from the Mediterranean, with a lifespan of 200 years. It plays a central role in the environmental, economic and social development of this region.

With unique properties, cork is 100% natural and fully degradable, renewable and recyclable.

200 YEARS

THE AVERAGE LIFESPAN OF A CORK OAK TREE

CO₂ RETENTION

FOR EACH TON OF CORK PRODUCED, THE CORK OAK FOREST RETAINS UP TO 73 TONS OF CO₂

9 YEARS

THE PERIOD OF TIME BETWEEN EACH CORK OAK HARVEST.

NO TREES ARE DAMAGED

OR CUT DOWN.

CORK HARVESTING

IS ONE OF THE HIGHEST PAID AGRICULTURAL JOBS IN THE WORLD.

100.000

DIRECT AND INDIRECT JOBS ARE CREATED BY THE CORK INDUSTRY.

AMAZING SUSTAINABILITY

ENVIRONMENT



No Trees are damaged or cut down during harvesting

The extraction of cork and its related industries are remarkably sustainable. This is because the tree is never cut down or damaged during the extraction process and the bark regenerates itself after each harvesting.



Positive ecological impact

For each ton of cork produced, the cork oak forest retains up to 73 tons of CO₂, helping to reduce Global Warming Potential (GWP).

ECONOMY



Rural areas economic engine

The cork oak forest is essential for the economic development of rural areas in the Mediterranean region, by creating jobs and activities related to the harvesting and treatment of cork. WWF estimates that more than 100,000 people are economically dependent of cork-related business activities.



One of the highest paid agricultural jobs

Cork harvesting is an activity that requires experience and high skills, to prevent damaging the tree during the process. Therefore this activity is one of the highest paid agricultural jobs in the world.

SOCIAL



Crossing generations

More than a job, harvesting is a handcraft work that requires a deep knowledge of the forest and the technique. Thus to be able to perform this activity takes several years of training, a know-how that crosses family generations.



Prevents rural desertification


Cork harvesting is a regular and cyclical process, creating a continuous activity that contributes to settle people in areas at risk of desertification.

WHY WICANDERS

SILENCE

Reduces the walking sound up to 53%.


WALKING SOUND



IMPACT RESISTANCE

Highest shock absorbing performance.


SHOCK ABSORBING



NATURAL THERMAL INSULATION


Optimal temperature all year round.

INFRARED FOOT TEMPERATURE




INDOOR AIR QUALITY

Compliance with the strictest indoor air quality standards after being tested on over 2000 potential chemicals.



WALKING COMFORT

Reduce effort on walking and decreases body fatigue.



10 | **cork** Go

13 | **cork** Essence

19 | **stone** Essence



cork

A world of solutions at
your feet.

cork Go



A budget friendly floating floor designed to bring comfort to residential spaces. The double cork layer in its structure reinforces the thermal and acoustic performance for a cozy atmosphere. Easy to clean and maintain, cork Go offers a 10 year warranty for domestic use.

Green ID



96%
of renewable content



Sustainably
sourced



80001631 GA01002 **Moment**



80001218 C822001 **Whim**



80001633 GA21003 **Desire**






80001636 GB01003 **Charm**



80001638 GB02002 **Allure**

TECHNICAL SOLUTION

PRODUCT INFORMATION		
Dimension	905 x 295 mm 35 7/8 x 11 7/8"	
Thickness	10,5 mm 13/32"	
Bevel	Not Beveled	
Finishing		
Locking system	 2G	
Class of use & Warranty		

- 1


PROTECTIVE SURFACE
- 2

GENUINE CORK VENEER
- 3

AGGLOMERATED CORK
- 4

HDF - HIGH DENSITY FIBERBOARD WITH CORKLOC
- 5

INTEGRATED CORK UNDERLAY



WHY CORK GO



Original cork visuals
One of a kind natural visuals.



Extra comfort
Double cork layer for a cozier and quieter space.



Durable and easy to maintain
a long-lasting floor with low maintenance.

cork Essence



Rich in style, charm and sophistication, cork Essence expresses its personality through the unique designs and formats aligned with modern interior design trends. In harmony with nature, each plank is unique. The ideal floor for creating ambiances full of charm, combined with the unique comfort of cork and the performance requirements of residential and light commercial areas.

Green ID




96%
of renewable content



Sustainably
sourced



80001246 C85L001 **Fashionable Cement**



80002243 O841002 **Originals Accent**



80002268 P832002 **Personality Chestnut**









80001300 C8G2001 **Novel Edge Natural**




80001651 I802002 **Identity Timide**



TECHNICAL SOLUTION

PRODUCT INFORMATION		
Dimension	905 x 295 mm 35 7/8 x 11 7/8"	
Thickness	10,5mm 13/32"	
Bevel	Not Beveled	
Finishing		
Locking system	 2G	
Class of use & Warranty	 	 

- 1
- PROTECTIVE SURFACE
- 2
- GENUINE CORK VENEER
- 3
- AGGLOMERATED CORK
- 4
- HDF - HIGH DENSITY FIBERBOARD WITH CORKLOC
- 5
- INTEGRATED CORK UNDERLAY



WHY CORK ESSENCE



Unique cork visuals
One of a kind natural visuals.



Higher resistance
Suitable for residential and light traffic commercial spaces.



Extra comfort
Double cork layer for added extra comfort.

TECHNICAL DATA SHEET

Technical Data Sheet	Standard	Unit	cork Go	cork Essence
Dimension (LxWxT)	-	-	905x295x10,5mm	905x295x10,5mm 1220x185x10,5mm
Mass per unit	-	Kgs / m ²	7,68	7,68
Packaging (box / pallet)	-	m ²	2,136 / 111,072	2,136 / 111,072 - 905x295x10,5mm 1,806 / 79,464 - 1220x185x10,5mm
Level of use Domestic	ISO 10874	Class	23	23
Level of use Commercial	ISO 10874	Class	-	31

GENERAL PROPERTIES - EN 12104 - EN 20326

Thickness, t -	EN ISO 24346	± 0,25	Complies	Complies
Length, l	EN ISO 24342	+/- 0.5%	Complies	Complies
Width, w	EN ISO 24342	+/- 0.10%	Complies	Complies
Squareness, q	EN ISO 24342	< 0.2	Complies	Complies
Straightness, s	EN ISO 24342	≤ 0,30	Complies	Complies
Openings, o	ISO 24337	max ≤ 0,20 mm	Complies	Complies
Height difference, h	ISO 24337	hmax ≤ 0,15 mm	Complies	Complies
Flatness of the panel (Length - concave / convex)	ISO 24337	concave ≤ 0,50 %, / convex ≤ 1,0 %	Complies	Complies
Flatness of the panel (Width - concave / convex)	ISO 24337	concave ≤ 0,15 %, / convex ≤ 0,20 %	Complies	Complies
Dimensional Stability	ISO 20326 (Anex C)	≤ 0.25 %	Complies	Complies

CLASSIFICATION PROPERTIES - EN 12104 - EN 20326

Wear resistance IP	EN 14354 (Annex D)	≥ 1000 cycles	Complies	-
		≥ 2 500 cycles	-	Complies
Castor chair resistance	ISO 4918	25 000 cycles	Complies	Complies
Simulated movement of a furniture leg	Visual	No damage shall be visible after testing with a foot type 2	Complies	Complies
Residual Indentation	EN ISO 24343-1	≤ 0,4 mm	Complies	-
		≤ 0,3 mm	-	Complies
Swelling	ISO 24336	≤ 20%	Complies	-
		≤ 18%	-	Complies

SAFETY PROPERTIES - EN 14041

Fire resistance	EN ISO 11925-2 + EN ISO 9239-1 : Class EN 13501-1	Class	Dfl-s1	Dfl-s1
Slip Classification	EN 13893	Class	DS	DS
Formaldehyde emission	EN 717-1	Class	E1	E1
Content pentachlorophenol (PCP)	EN 14041 Annex B	mg/kg	Undetectable	Undetectable

ADDITIONAL PROPERTIES

Impact sound reduction	EN ISO 10140	dB (Δ Lw)	16	16
Walking noise	IHD-W431	dB %	13,2 51,6	13,2 51,6
Thermal resistance (Thermal conductivity)	EN ISO 10456	m2·K/W	R≤ 0,150	R≤ 0,150

stone Essence



Feel the walking comfort and the exceptional thermal insulation, even when walking barefoot. Wicanders stone offers unique stone visuals with the unmatched comfort of cork that will elevate any space while providing a warm atmosphere all year round. The selected stone visuals will give your space a natural look and feel. Floating floor with multilayer cork structure that combines the unmatched properties of cork with the beauty of selected stone visuals that give this solution a natural look and feel.

stone
Our performance.
Your comfort.

Green ID



96%
of renewable content



PVC
free



80001452 D88Z001 **Beton Nordic**




80001458 D89B001 **Beton Corten**



80001460 D89D001 **Concrete Nordic**



80001461 D89E001 **Concrete Urban**



80001463 D89G001 **Concrete Midnight**



80001464 D89H001 **Azulejo Sand**



Concrete Nordic



80001465 D89I001 **Azulejo Cityzen**











80001466 D89J001 **Azulejo Forest**




Beton Corten

TECHNICAL SOLUTION

PRODUCT INFORMATION		
Dimension	905 x 295 mm 35 7/8 x 11 7/8"	
Thickness	10,5 mm 13/32"	
Bevel	Not Beveled	
Finishing		
Locking system	 2G	
Class of use & Warranty	<div> 23  </div> <div> 32  </div>	

- 1
- PROTECTIVE WEAR LAYER
- 2
- HIGH RESOLUTION IMAGE
- 3
- AGGLOMERATED CORK
- 4
- HDF - HIGH DENSITY FIBERBOARD WITH CORKLOC
- 5
- INTEGRATED CORK UNDERLAY



WHY STONE ESSENCE



Highly realistic designs
Stone like visuals with all the benefits of cork.



Durable and easy to maintain
A long-lasting floor with low maintenance.



Thermal and acoustic comfort
Provides a comfortable and silent environment all year round.

TECHNICAL DATA SHEET

stone Essence	Standard	Unit	Value
Dimension (LxWxT)	-	-	905x295x10,5mm
Mass per unit	-	Kgs / m ²	7,11
Packaging (box / pallet)	-	m ²	2,136 / 76,896
Level of use Domestic	ISO 10874	Class	23
Level of use Commercial	ISO 10874	Class	32

General properties - EN 12104 - EN 20326

Thickness, t -	EN ISO 24346	± 0,25	Complies
Length, l	EN ISO 24342	+/- 0.5%	Complies
Width, w	EN ISO 24342	+/- 0.10%	Complies
Squareness, q	EN ISO 24342	< 0.2	Complies
Straightness, s	EN ISO 24342	≤ 0,30	Complies
Openings, o	ISO 24337	max ≤ 0,20 mm	Complies
Height difference, h	ISO 24337	hmax ≤ 0,15 mm	Complies
Flatness of the panel (Length - concave / convex)	ISO 24337	concave ≤ 0,50 %, / convex ≤ 1,0 %	Complies
Flatness of the panel (Width - concave / convex)	ISO 24337	concave ≤ 0,15 %, / convex ≤ 0,20 %	Complies
Dimensional Stability	ISO 20326 (Anex C)	≤ 0.25 %	Complies

Classification properties - EN 12104 - EN 20326

Wear resistance IP	EN 14354 (Annex D)	≥ 5 0000 cycles	Complies
Castor chair resistance	EN 425	25 000 cycles	Complies
Residual Indentation	EN ISO 24343-1	≤ 0,3 mm	Complies
Swelling	ISO 24336	≤ 18%	Complies
Locking system	ISO 24334	Long side ≥ 1 kN/m Short side ≥ 2 kN/m	Complies














Safety properties - EN 14041

Fire resistance	EN ISO 11925-2 + EN ISO 9239-1 : Class EN 13501-1	Class	C fl-s1
Slip Classification	EN 13893	Class	DS
Formaldehyde emission	EN 717-1	Class	E1
Content pentachlorophenol (PCP)	EN 14041 Annex B	mg/kg	Undetectable











Additional properties

Impact sound reduction	EN ISO 10140	dB (Δ Lw)	16
Walking noise	IHD-W431	dB %	13,2 51,6
Thermal resistance (Thermal conductivity)	EN ISO 10456	m2.K/W	R≤ 0,150











PICTOGRAMS

 2G	Floating 2G 2G locking system is a strong and robust mechanical locking system installed by angling of both long and short side.
 5Gi	Floating 5Gi A locking system based on a single action installation method suitable for all types and widths of floor products.
 2G PressFit	Floating 2G PressFit A system that combines 2G strong and robust mechanical locking system on the short side, with the PressFit revolutionary compression system on the long side, for a strong, easy and fast installation.
	Heavy Traffic Residential areas
	Moderate Traffic Commercial areas
	Medium Traffic Commercial areas
	Heavy Traffic Commercial areas
	Warranty
	XtraMatt surface has the resistance and performance of a UV finish, focused on environmental friendly properties and ease of maintenance.
	XtraMatt+ surface is a High Resistance Acrylic UV finish suitable for residential and light commercial areas.
	Suitable for medium traffic commercial areas.
	Suitable for heavy traffic commercial areas.
	NPC surface finish (Natural Power Coat) is suitable for the most demanding domestic areas and commercial areas with moderate traffic, achieving a class of 32 (ISO 10874) and AC6 (EN 13329).

CERTIFICATIONS

	cork Go	cork Essence	stone Essence
	✓	✓	✓
	✓	✓	●
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	7	7	7
	8	8	8

* upon request

	CE CE marking indicates conformity with health, safety and environmental standards for products sold within the European Economic Area (EEA).
	DAS KORK Assures the quality of cork products, as well as the optimization of manufacturing processes and the support of research projects.
	FRENCH REGULATION ON VOC EMISSIONS French certification that classifies products according to their level of voc emissions. Our products have been classified at the highest level (A+).
	TÜV-PROFICERT Tuv-Proficert is a transnational certificate for voc-emission and air quality, certifying that a product complies with different national regulations.
	BLUE ANGEL Voluntary certification that follows strict environmental standards and is recognized as a reference guide for a more sustainable way of life.
	GREENGUARD CERTIFICATION North-american certification that identifies products that have low chemical emissions, improving the air in which they are used. Our products are awarded with the GOLD certification.
	EPD (ENVIRONMENTAL PRODUCT DECLARATION) Third-party independent evaluation that reports environmental data of products based on their life cycle assessment.
	F4 STARS Japan’s regulation for formaldehyde emissions. Our products have F4stars (extremely low emissions).
	LEED Wicanders products contribute with points in the following categories: Materials and Resources / Indoor Environmental Quality.
	BREEAM Wicanders products contribute with points in the following categories: Health and well being / Materials.



Amorim Cork Flooring, S.A.

Rua do Ribeirinho 202 - P.O. Box 13

4536-907 S. Paio de Oleiros - Portugal

T. +351 22 747 56 00 E. info.acf@amorim.comwww.wicanders.com

DE	Amorim Deutschland GmbH	(+49) 4221 5 93-01	info.acf.de@amorim.com
BENE LUX	Amorim Benelux B.V.	(+31) 166 604 111	info.acf.bnl@amorim.com
AT	Amorim Deutschland GmbH	(+43) 1 54 51 65 10	info.acf.at@amorim.com
CH	Amorim Flooring Switzerland AG	(+41) 41 726 20 20	info.acf.ch@amorim.com
PT	Amorim Cork Flooring, S.A.	(+351) 227 475 600	info.acf@amorim.com
ES	Amorim Cork Flooring, S.A.	(+351) 227 475 600	info.acf.es@amorim.com
FR	Amorim Cork Flooring, S.A.	(+33) 800 914 848	info.acf.fr@amorim.com
DK	Timberman Denmark A/S	(+45) 995 252 52	timberman@timberman.dk
PL	Dom Korkowy, Sp. z o.o.	(+48) 126 379 639	krakow@domkorkowy.pl
US	Amorim Flooring North America	(+1) 410 553 60 62	info.acf.us@amorim.com
RU	Amorim Flooring Rus, OOO	(+7) 495 280 7860	info.acf.ru@amorim.com
IT	Amorim Cork Flooring, S.A.	(+39) 800 790 805	info.acf.it@amorim.com
FI	Korkkitrio Oy	(+358) 50 554 2616	wicandersmyynti@korkkitrio.fi
SW	Amorim Flooring Sweden	(+46) 311 077 40	info.acf.se@amorim.com
CA	Amorim Flooring Canada	(+1) 905 366 7328	info.acf.ca@amorim.com



INVESTORS IN PEOPLE™
We invest in people Standard

Recognised by **EFQM**
★★★★ 2021

AMORIM